



Specification Sheet

Z-Slip

Features:

- Direct thermal, paper and polypropylene label combination
- Excellent print quality
- Unique construction protects printable side from chemicals and keeps information secure.
- Available in white (65091RM)

Suggested Applications:

- Packing Slip applications
- Invoice Documents
- Personalized messaging for internet or catalog gift deliveries
- Certificate of conformance
- Commercial invoice for customs declarations
- Material Safety Data Sheets

Material Construction:

	Description	Caliper
Facestock	White smooth direct thermal topcoated paper	5.9 mil
Adhesive	All-temp, acrylic-based	0.9 mil
Facestock	Clear polypropylene	2.1 mil
	Total	8.9 mil +/- 10%

Temperature Performance:

- Minimum Application Temperature: 23° F (-5° C)
- Service Temperature: -20° F to 131° F (-29° C to 55° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Recommended for applications with minimal outdoor use





Specification Sheet

Z-Slip

Applications with Chemicals

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
DT	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

