

# C37

Barcode CCD scanner

RS232

Keyboard Wedge

 USB



### + Related products



#### OPL7836

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB



#### OPR2001

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB
- With stand



#### OPR3001

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB



## Operating indicators

- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

## Operating keys

- Entry options:  
1 scan key

## Communication

- RS232: DB9 PTF connector with external power supply
- Keyboard Wedge: MiniDIN6 F/M connector
- USB: Ver. 1.1, HID/VCP, USB-A connector

## Power

- Voltage requirement: 5V  $\pm$  10% (Keyboard Wedge and USB), 6V (min. 4.5, max. 6.6V) (RS232)

## Barcode scanner Optics

- Light source: 630 nm red LED
- Scan method: CCD linear Sensor 2500 Pixels
- Scan rate: 200 scans/sec
- Trigger mode: Manual, auto-trigger
- Reading pitch angle: -35 to 0°, 0 to +35°
- Reading skew angle: -70 to -20°, 20 to 70°
- Reading tilt angle: -20 to 0°, 0 to +20°

## Supported Symbologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Composite codes, MicroPDF417, PDF417

## Durability

- Temperature in operation: 0 to 50 °C / 32 to 122 °F
- Temperature in storage: -20 to 60 °C / -14 to 140 °F
- Humidity in operation: 5 - 95% (non-condensing)
- Humidity in storage: 5 - 95% (non-condensing)
- Ambient light immunity: Fluorescent 10,000 lx max, Direct sun 10,000 lx max, Incandescent 10,000 lx max
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Vibration test: 10 - 100 Hz with 2G for 1 hour
- Protection rate: IP 42

## Physical

- Dimensions (w x h x d):  
79 x 60 x 170 mm / 3.11 x 2.36 x 6.69 in
- Weight body: Ca. 90 g / 3.2 oz (excl. cable)
- Case: ABS, Black, White

## Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS

## Enclosed items

- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A (for RS232)

## Models

- Interface versions: RS232, Keyboard Wedge, USB
- Color versions: Black, White

Copyright © Opticon. Alle Rechte vorbehalten. Inhabiter Technologie und Innovationen. [www.opticon.com](http://www.opticon.com) Wir sind stolz auf unsere Produkte und unsere Mitarbeiter.

- USA (Hauptvertrieb): Philadelphia
- Frankreich: Paris
- Deutschland: Düsseldorf
- Italien: Castel Maggiore (BO)
- Spanien: Valencia
- Schweden: Malmö
- Großbritannien: Luton, Bedfordshire
- USA: NJ, Newark, NJ
- Japan: Osaka City

- Taiwan: Taipei
- Philippinen: Manilla
- Australien: Sydney
- Brasilien: São Paulo

Opticon Consumer GmbH  
Hauptstrasse 63  
52728 Düsseldorf,  
Deutschland  
Telefon: +49 (0)2129 49 495-0  
Fax: +49 (0)2129 49 495-333  
E-Mail: [sales@opticon.com](mailto:sales@opticon.com)  
Internet: [www.opticon.com](http://www.opticon.com)

**OPTICON**  
[WWW.OPTICON.COM](http://WWW.OPTICON.COM)